




HDS-E 8/16-4 M 24 kW

The electrically heated HDS E 8/16-4 M hot water high-pressure cleaner impresses with 24 kW heating output and high energy efficiency wherever exhaust gases are undesirable or not permitted.



1 Particularly high work temperature

- Large water reservoir (max. 85°C).
- Up to 45°C in continuous operation under full load or 70°C with Servo Control.

2 Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings.

- Effortless operation at last: the EASY!Force high-pressure gun.
- EASY!Lock quick-release couplings: durable and robust. And five

3 Servo control

- For delivering a significantly higher water temperature to the accessories.



HDS-E 8/16-4 M 24 kW

- Economical ecoefficiency mode
- Tilting aid
- Two cleaning agent tanks with automatic rinsing

Technical data

Order no.	1.030-904.0	
EAN code	4054278169002	
Flow rate	l/h	300 - 760
Pressure	bar / MPa	30 - 160 / 3 - 16
Temperature (for supply 12 °C)	°C	45 / 85
Connection load	kW	29.5
Number of simultaneous users	1	
Mobility	Low	
Weight	kg	122.1
Dimensions (L × W × H)	mm	1330 × 750 × 1060

Equipment

Spray gun	EASY!Force Advanced	
High-pressure hose	m	10 / DN 6, 250 bar
Spray lance	mm	1050
Power nozzle	■	
Servo control	■	
Zero-emissions electric heater	■	
Anti-twist system (AVS)	-	
Control panel with display light	■	
Pressure cut-off	■	
2 cleaning agent tanks	■	
■ Included in the scope of supply.		